



LIGHT WEIGHT



LOW ENERGY



NO NOISE



EASY INSTALL

WATERPROOF



/

	1.25 mm	1.6 mm	2.6 mm
	SMD	SMD	SMD
	640,000 160,000	360000 90000	147456 36864
(W×H (mm	250 × 250	250 × 250	250 × 250
(W×H (mm	500 × 500 × 73.5	500 × 500 × 73.5	500 × 500 × 73.5
( W H (mm	1000 × 1000 × 125	1000 × 1000 × 125	1000 × 1000 × 125
(W×H	2 × 2	2 × 2	2 × 2
(W×H	200 × 200	150 × 150	96 × 96
(W×H	400 × 400	300 × 300	192 × 192
	7.5kg/	7.5kg/	7.5 kg/
	47.2 kg/m <sup>2</sup> *	47.2 kg/m <sup>2</sup> *	47.2 kg / m <sup>2</sup> *
	14-16 bit	14-16 bit	14-16 bit
	281 trillion	281 trillion	281 trillion
	20000 : 1	20000 : 1	20000 : 1
	72 - 120 w/	72 - 120 w/	50 - 80 w/
	240 w/	240 w/	160 w/
	-30 - 50 /10% - 90%	-30 - 50 /10% - 90%	-30 - 50 /10% - 90%
	-30 - 60 /10% - 95%	-30 - 60 /10% - 95%	-30 - 60 /10% - 95%
	400 - 600 nits	400 - 600 nits	600 - 1000 nits
	3840 Hz	3840 Hz	3840 Hz
	140°	140°	140°
	140°	140°	140°
	100000 Hrs	100000 Hrs	100000 Hrs
IP	IP65	IP65	IP65
	CE, EMC, LVD, CCC CC	CE, EMC, LVD, CCC CC	CE, EMC, LVD, CCC CC

>  
>>  
>>  
>

