

/

	2.9 mm
	SMD
	112,896 28,224
	250 × 250
	500 × 500 × 86
	2 × 22

>	>	>
>	>	>
>	>	>
>	>	>

/

	3.9 mm	4.6 mm	5.2 mm
	SMD	SMD	SMD
	65536 16384	46,656 11,664	36,864 9, 216
(W×H)()	250 × 250	250 × 250	250 × 250
(W×H ()	500 × 500 × 86	500 × 500 × 86	500 × 500 × 86 *
(W×H)	2 × 2	2 × 2	2 × 2
(W×H)	64 × 64	54 × 54	48 × 48
(W×H)	128 × 128	108 × 108	96 × 96
	7.9 kg/	7.9 kg/	7.9 kg/
	31.6 kg/m ²	31.6 kg/m² *	31.6 kg/m ² *
	14 - 16 bit	14 - 16 bit	14 - 16 bit
	281 trillion	281 trillion	281 trillion
	4000:1	4000:1	4000 : 1
	55 - 92 w/	55 - 92 w/	55 - 92 w/
	184 w/	184 w/	184 w/
	-30 - 50 / 10% - 90%	-30 - 50 / 10% - 90%	-30 - 50 / 10% - 90%
	-30 - 60 / 10% - 95%	-30 - 60 / 10% - 95%	-30 - 60 / 10% - 95%
	5000 nits	5000 nits	5000 nits
	3840 Hz	3840 Hz	3840 Hz
	140°	140°	140°
	120°	120°	120°
	100000 Hrs	100000 Hrs	100000 Hrs
	20	20	20
	16	16	16
(-: ;+:)	-10°/-5°/0°/+5°	-10°/-5°/0°/+5°	-10°/-5°/0°/+5°
	IP 65	IP 65	IP 65
	CE, EMC ClassA, ETL, RoHS *	CE, EMC ClassA, ETL, RoHS *	CE, EMC ClassA, ETL, RoHS *

> > > >

>
>
>
>
>
>
>
>
>
>
>